



Marine & Offshore
Division

Certificate number: 44860/A0 BV

File number: ACM 135/2769/01

Product code: 2161H

This certificate is not valid when presented without the full attached schedule composed of 7 sections

www.veristar.com

TYPE APPROVAL CERTIFICATE

This certificate is issued to
HY-LOK CORPORATION
BUSAN - KOREA (REPUBLIC OF)

for the type of product
PIPE FITTINGS
HY-LOK Tube Fitting

Requirements:

- BUREAU VERITAS Rules for the Classification of Steel Ships

This certificate is issued to attest that BUREAU VERITAS did undertake the relevant approval procedures for the product identified above which was found to comply with the relevant requirements mentioned above.

This certificate will expire on: 16 Nov 2021

For BUREAU VERITAS,
At BV PUSAN, on 16 Nov 2016,
Chang-uk HONG



This certificate remains valid until the date stated above, unless cancelled or revoked, provided the conditions indicated in the subsequent page(s) are complied with and the product remains satisfactory in service. This certificate will not be valid if the applicant makes any changes or modifications to the approved product, which have not been notified to, and agreed in writing with BUREAU VERITAS. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/they being placed on board vessels to which the amended regulations or standards apply. This certificate is issued within the scope of the General Conditions of BUREAU VERITAS Marine & Offshore Division available on the internet site www.veristar.com. Any Person not a party to the contract pursuant to which this document is delivered may not assert a claim against BUREAU VERITAS for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgement, fault or negligence committed by personnel of the Society or of its Agents in establishment or issuance of this document, and in connection with any activities for which it may provide.

The electronic version is available at: <http://www.veristarpm.com/veristarnb/jsp/viewPublicPdfTypepec.jsp?id=kqbbaur0pz>
BV Mod. Ad.E 530 October 2014

This certificate consists of 3 page(s)

THE SCHEDULE OF APPROVAL

1. PRODUCT DESCRIPTION

HY-LOK Tube Fittings

1.1 Design

Double ferrule bite and compression type tube fittings

1.2 Models

CUA, CUR, CLA, CTA, CXA, CBU, CMC-N, CMCT, CMC-R, CMC-G, COM, CBMC, CLMA, CLMB, CRTM, CBTM, CFC, CGC, CBFC, CLF, CRTF, CR, CBR, CAL, CRTA, CAM, CAF, CAM-G, CAM-U, CAMOS, CAMF, SAPW, CPC, CPR, CSRA, CSL, CFTC, CIAF, CFU, CBFU, CFA, CSC, CSLA, CSRT, CSBT, CSLB, COS, COP, CWC, CLW, CSWC, CLSW, CBUW, CHBUW, CPA, CCA, CRMTU, CRMTT, CCFE, CCEUR, CDF, CSFC, CN, CFF, CFB, CFS, CNFS, CI, CCL, CBRE, H-SPBFM, CFTA, CFSC & CFSP.

1.3 Ratings

Max. Design pressure	950 bar, depending on size
Temperature range (°C)	Stainless steel: - 196 up to 649 Brass: -54 up to 204 Alloy 400: -54 up to 427
Size (mm / inch)	3 ~ 25 / 1/8" ~ 1"

1.4 Materials

Stainless steel	ASTM A479 Type 316 ASTM A182 F316
Brass	KS/JIS H3250 C3604BD, C3771BE ASTM B16, B124, B283
Alloy 400	ASTM B164 (N04400) ASTM B564 (N04400)

When other choices of materials are used per manufacturer's recommendations, the BV agreement is to be obtained.

2. DOCUMENTS AND DRAWINGS

- Design specification sheet N° 200TF-DS Rev.4 dated 15/07/2014
- Design plan N° 200TF-DP Rev.4 dated 08/07/2014
- Catalogue N° H-200TF

No departure from the above documents shall be made without the prior consent of the Society. The manufacturer must inform the Society of any modification or changes to these documents and drawings.

3. TEST REPORTS

Tests carried out, witnessed by an IACS member surveyor:

- Tightness test reports dated 23/01/2007
- Repeated assembly test dated 02/02/2007
- Burst test at 4 times the max working pressure report dated 05/02/2007
- Vibration test and pressure pulsation test report dated 09/10/2007 & 26/10/2007
- Pull-out test report dated 14/02/2007
- Vacuum test report detade 16/02/2007

4. APPLICATION / LIMITATION

- 4.1 May be used on board for the services of class I, II, III piping systems including: hydraulic oil, lubrication oil, fuel oil, gas, steam & condensate, fresh & sea water and sanitary.
- 4.2 The reduction factors according to the manufacturer's specification are to be observed.
- 4.3 In all cases, the associated pipes are to be suitably supported and anchored. The joints are to be at any time accessible, excepting inside tanks where permitted by the BUREAU VERITAS Rules.
- 4.4 The wall thickness and material of the tubes are to be in accordance with BUREAU VERITAS Rules.
- 4.5 The selection of pipes, fittings and seals must be compatible with the fluid to be conveyed and the maximum working temperature according to the manufacturer's recommendations.
- 4.6 The use of stainless steel is restricted as per BUREAU VERITAS Rules.
- 4.7 Threaded bulkhead fittings are not approved through watertight or fire bulkheads.

4.8 Assembly instructions given by the manufacturer are to be complied with.

5. PRODUCTION SURVEY REQUIREMENTS

5.1 The products are to be supplied by **HY-LOK CORPORATION** in compliance with the type described in this certificate.

5.2 This type of product is within the category HBV of Bureau Veritas Rule Note NR320 and as such does not require a BV product certificate.

5.3 **HY-LOK CORPORATION** has to make the necessary arrangements to have its works recognised by Bureau Veritas in compliance with the requirements of NR320 for HBV products.

HY-LOK CORPORATION has declared to Bureau Veritas the following production site:

HY-LOK CORPORATION: #1467-1, Songjeong-dong, Gangseo-gu, BUSAN, KOREA (REPUBLIC OF)

6. MARKING OF PRODUCT

Each fitting shall be at least marked with:

- Manufacturer's name or logo
- Type designation
- Size
- Material

7. OTHERS

It is **HY-LOK CORPORATION's** responsibility to inform shipbuilders or their sub-contractors of the proper methods of fitting, use and general maintenance of the approved equipment and the conditions of this approval.

*** END OF CERTIFICATE ***